

DELIVERY REGULATOR FOR VEHICLE AND TRUCK WITH COMMON-RAIL ELECTRONIC DIESEL SYSTEM



P.N.: CD2000-545

- Power enhances from 20% to 30%
- Fuel consumption is cut off
- 3-phase switching: Normal, Boosted -, Boosted +
- Power is regulated by software installed in your PC and USB programmer (not supplied)
- It does not change ignition control parameters
- It may be put into service on other vehicles

ITEMS ON REQUEST:



Cable to connect Rail pressure sensor to Bosch system (except Audi-Mercedes)

P.N.: CD2000/C3



Cable to connect Rail pressure sensor to Delphi -Siemens

P.N.: CD2000/C4



Cable to connect Rail pressure sensor to Bosch (Audi-Mercedes)

P.N.: CD2000/C5

	COM4	*	Cornel	_			_M						
				0 1 2		0	oroi	VA	A	DIESEL			
			0		3	4	5	6	7	8			
	PUNTO DI		Term	ione):()	(Vin00								Giri/min
LAVORO		0	17	20	24	28	32	36	40	43	45		
no/gio giúltim Percentuale uscita in decremento (3)													
	15	4000	0	0	12	18	20	20	20	15	10	5	
	16	3790	0	0	12	18	20	20	20	15	10	5	
	17	3629	0	0	12	18	20	20	20	15	10	5	Tensione in Ingresso
	20	3000	0	0	12	10	20	20	20	15	10	15	
	21	2857	0	0	12	18	20	20	20	15	10	5	
	24	2500	0	0	12	18	20	20	20	15	10	5	
	30	2000	0	0	12	18	20	20	20	15	10	6	Percentuale in decremento
	30	1010	0	0	12	10	20	20	20	15	10	8	
	40	1500	0	0	12	18	20	20	20	15	10	5	
	48	1290	0	0	12	18	20	20	20	15	10	5	
3.5	imiti dei Parametri ss/giro: 2 - 200 giri/min: 30000 - 300 Panzione: 1 - 50 Parcentuali: 1 - 100												Tensione in Uscita

PC software and USB programmer P.N.: CD2000/TTL